

LUKOIL GENESIS SPECIAL C2 0W-30

Synthetic Mid-SAPS engine oil for passenger cars

Approvals

- PSA B71 2312

Meets requirements

- ACEA C2

Product description

Synthetic engine oil, specially developed for up-to-date gasoline and diesel engines of passenger cars with particulate filter. Produced on the basis of high quality synthetic base oils using advanced additive technology with a reduced sulphated ash content.

Application

Designed for use in gasoline and diesel engines of cars of the Peugeot-Citroen concern, as well as other vehicles requiring oil with ACEA C2 performance and SAE 0W-30 viscosity grade.

Benefits

EASY START

Excellent low-temperature pumpability

MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

COMPATIBILITY WITH AFTERTREATMENT SYSTEM

Compatible with exhaust aftertreatment devices, which are sensitive to sulphated ash content

FUEL ECONOMY

Superior fuel economy thanks to lower HTHS viscosity and potential to reduce emissions

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	840
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	9.5
Viscosity index	ASTM D2270	175
Dynamic viscosity (CCS) at -35°C, mPa·s	ASTM D5293 / GOST R 52559	5,798
Total Base Number, mg KOH/1 g oil	ASTM D2896	6.9
Pour Point, °C	ISO 3016	<-42
Flash Point, COC, °C	ISO 2592	>210