

Teboil Diamond 5W-30

Teboil Diamond 5W-30 is high quality, fully synthetic long life motor oil for passenger cars and vans with gasoline or diesel engine.

Applications

Teboil Diamond 5W-30 is fully synthetic long life motor oil. It is specially developed for GM (Opel, SAAB) engines which require GM-LL-A-025 or GM-LL-B-025 specification. It is also suitable for use in other manufacturer engines according to its specifications.

Performance features and benefits

Diamond 5W-30 protects engine against wear and keeps it clean during the whole drain interval. Because of excellent cold temperature features, oil succeeds to maintain its flow ability even in hard winter conditions and ensures engines optimal lubrication immediately from cold start.

Typical physical characteristics

Teboil Diamond	5W-30	Unit	Method
Density @ 20 °C	850	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	70	mm ² /s	ASTM D 445
Viscosity @ 100 °C	12,0	mm ² /s	ASTM D 445
Viscosity @ -30 °C	6000	mPa.s	ASTM D 5293
Viscosity index	167		ASTM D 2270
Flash point	222	°C	ASTM D 92
Pour point	-39	°C	ASTM D 97

Specifications and approvals

API SL/CF; ACEA A3/B4

GM-LL-A/B-025; BMW LL-01; MB 229.3, 229.5; VW 502.00, 505.00

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 8.1.2013

Postal address

PL 57
01511 Vantaa

Address

Äyritie 20
01510 Vantaa

Phone

+358(0)204 7001

Fax

(09) 643 865

Internet pages

www.teboil.fi

Business ID

0114795-2