

## LUKOIL TRANSMISSION LDI 75W-80

High performance fully synthetic transmission oil with fuel economy properties

### Specifications

- MAN 341 Type Z4
- MAN 341 Type E3
- VOLVO 97305
- DAF
- API GL-4
- ZF TE-ML 01L/02L/02D/08/16K
- IVECO 18-1807 Classe MGS1
- Renault

### Product description

Synthetic transmission oil with extremely long drain interval for manual transmissions. Modern high performance anti-wear and anti-corrosion additives create a stable oil film on transmission parts and help to extend transmission life.

### Application

Recommended for synchronized manual transmissions with or without interarders and medium-duty final drives which require the use of both mineral and synthetic oils. The product is specially adapted for use in mechanical transmissions of commercial vehicles and is perfectly compatible with any type of synchronizers, including those made of molybdenum, carbon and agglomerate.

### Benefits

#### OXIDATION RESISTANCE

Provides excellent thermal oxidative stability and maintains all properties even in the event of extended drain intervals

#### STABLE VISCOSITY

Stable viscosity over entire period of operation due to the exceptional resistance to degradation of the viscosity modifier

#### EXCELLENT SEAL COMPATIBILITY

Leading to benefits of for component protection, maintenance of heattransfer and efficiency combined with reduced risk from seal leakage

#### MAXIMUM PROTECTION

Thanks to improved anti-wear properties and excellent compatibility with any type of synchronizer, high protection of transmission mechanisms is provided, which allows to increase the oil change interval

The product name in an order: Transmission oil LUKOIL TRANSMISSION LDI 75W-80, STO 79345251-200-2019

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	851
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	9.8
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	58.3
Brookfield Viscosity at -40 °C, mPa·s	ASTM D5293	73,380
Viscosity index	ASTM D2270	157
Flash Point, COC, °C	ASTM D92	230
Pour Point, °C	ASTM D97	-42