

Teboil Silver 10W-40

Teboil Silver 10W-40 is good quality semi-synthetic motor oil for passenger cars and vans with gasoline or diesel engine.

Applications

Teboil Silver 10W-40 is suitable for year around use in passenger cars and vans with gasoline or diesel engine, even when equipped with turbocharger or catalizator.

Performance features and benefits

Oil has good hot and cold temperature performance. Tailored additives give it good properties against wear, oxidation and deposits.

Typical physical characteristics

Teboil Silver	10W-40	Unit	Method
Density @ 20 °C	866	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	92	mm ² /s	ASTM D 445
Viscosity @ 100 °C	13,7	mm ² /s	ASTM D 445
Viscosity @ -25 °C	5200	mPa.s	ASTM D 5293
Viscosity index	152		ASTM D 2270
Flash point	214	°C	ASTM D 92
Pour point	-39	°C	ASTM D 97

Specifications and approvals

API SL/CF; ACEA A3/B3/B4
BMW LL-98; MB 229.1; VW 502.00, 505.00

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 8.1.2013

Postal address
PL 57
01511 Vantaa

Address
Äyritie 20
01510 Vantaa

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2