

LUKOIL GENESIS SPECIAL SPX 5W-30

Fully synthetic energy-conserving engine oil

Meets requirements

- API SP, SP-RC
- ILSAC GF-6A

Product description

Multigrade fully synthetic engine oil of the latest generation, designed in accordance with modern requirements to fuel economy. The oil is intended for use in modern high-performance (both non-charged and turbocharged) gasoline engines of passenger cars and light trucks.

Application

Recommended for use in gasoline engines of Japanese, American and Korean manufacturers, which require oils with API SP and/or ILSAC GF-6A performance level and SAE 5W-30 viscosity grade. Can also be used in engines, which require oils of previous API categories: SN, SM, SL or below.

Benefits

ADVANCED FUEL ECONOMY

Excellent fuel economy due to optimal viscometric characteristics

EASY COLD START

Excellent low-temperature properties provide easy cold start

RELIABLE PROTECTION

High oil film thickness over entire drain interval

HIGH VISCOSITY INDEX

Stable viscosity across a broad temperature range

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL SPX 5W-30, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

| Property | Test methods | Value |
|---|---------------------------|--------|
| Kinematic viscosity at 100 °C, mm ² /s | ASTM D445 | 10.8 |
| Viscosity index | ASTM D2270 | 161 |
| Dynamic viscosity (CCS) at -30°C, mPa·s | ASTM D5293 / GOST R 52559 | 5,800 |
| Dynamic viscosity (MRV) at -35°C, mPa·s | ASTM D4684 / GOST R 52257 | 30,100 |
| Total Base Number, mg KOH/1 g oil | ASTM D2896 | 7.2 |
| Sulphated ash, % | ASTM D874 | 0.74 |
| Noack evaporation loss, % | ASTM D5800 / DIN 51581-1 | 12.1 |
| Flash Point, COC, °C | ASTM D92 | 226 |
| Pour Point, °C | GOST 20287 B | -42 |