

## LUKOIL GEYSER MM 10W

High Quality Oil for Off-Road Vehicles

### Specifications

- Allison C-4
- API MT-1
- Komatsu KES 07.868-1
- API CF
- Caterpillar TO-4
- ZF TE-ML 03C

### Product description

Universal oil for off-road vehicle produced on high quality base oil with involvement multifunctional additive package, which provides smooth operation of gearboxes frictional components.

### Application

Used in axle and final drives, as well as transmission components of heavy duty applications, including off-road vehicles, where CAT TO-4 and Komatsu KES 07.868.1 oils are required. Can also be used in hydraulic systems, wet disk brakes and diesel engines (4T, 2T).

### Benefits

#### UNIVERSAL APPLICABILITY OF OILS

Possibility of application in various friction units

#### SUPERIOR FRICTION CHARACTERISTICS

Provides stable and smooth operation of friction components

#### OXIDATION RESISTANCE

Contains corrosion inhibitors and protects ferrous and non-ferrous metals

The product name in an order: Hydraulic oil LUKOIL GEYSER MM 10 (SAE 10W), TU 0253-013-79345251-2008

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

| Property  | Test methods            | Value |
|---|-------------------------|-------|
| Density at 20 °C, kg/m <sup>3</sup>               | ASTM D1298 / ASTM D4052 | 880   |
| Kinematic viscosity at 100 °C, mm <sup>2</sup> /s | ASTM D445               | 7.2   |
| Viscosity index                                   | ASTM D2270              | 110   |
| Total Base Number, mg KOH/1 g oil                 | GOST 11362              | 9.6   |
| Flash Point, COC, °C                              | ASTM D92                | 233   |
| Pour Point, °C                                    | GOST 20287 B            | -37   |