

LUKOIL GEYSER MM 30

High Quality Oil for Off-Road Vehicles

Specifications

- Allison C-4
- API MT-1
- Komatsu KES 07.868-1
- API CF
- Caterpillar TO-4
- ZF TE-ML 03C/07F

Product description

Universal oil for off-road vehicle produced on high quality base oil with involvement multifunctional additive package, which provides smooth operation of gearboxes frictional components.

Application

Used in axle and final drives, as well as transmission components of heavy duty applications, including off-road vehicles, where CAT TO-4 and Komatsu KES 07.868.1 oils are required. Can also be used in hydraulic systems, wet disk brakes and diesel engines (4T, 2T).

Benefits

UNIVERSAL APPLICABILITY OF OILS

Possibility of application in various friction units

SUPERIOR FRICTION CHARACTERISTICS

Provides stable and smooth operation of friction components

OXIDATION RESISTANCE

Contains corrosion inhibitors and protects ferrous and non-ferrous metals

The product name in an order: Hydraulic oil LUKOIL GEYSER MM 30 (SAE 30), TU 0253-013-79345251-2008

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D1298 / ASTM D4052	891
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	11.3
Viscosity index	ASTM D2270	100
Total Base Number, mg KOH/1 g oil	GOST 11362	9.5
Flash Point, COC, °C	ASTM D92	244
Pour Point, °C	GOST 20287 B	-26