

## LUKOIL GEYSER MM 60

High Quality Oil for Off-Road Vehicles

### Specifications

- Caterpillar FD-1

### Product description

Universal oil for off-road vehicle produced on high quality base oil with involvement multifunctional additive package, which provides smooth operation of gearboxes frictional components.

### Application

Intended for use in axle and final drives, as well as transmission components of heavy duty applications, including off-road vehicles, tracked tractors with an upper drive roller. Recommended for use in Caterpillar off-highway equipment where Cat FD-1 is required. Not recommended for use with friction materials and hydraulic systems.

### Benefits

#### EXCELLENT ANTIWEAR PROPERTIES

Provides superior wear protection and extends the life of bearings and gears

#### METAL PROTECTION

Sustained film thickness even at high loads

#### EXTENDED DRAIN INTERVAL

Extended drain interval comparing to regular TO-4 oils

#### OXIDATION RESISTANCE

Contains corrosion inhibitors and protects ferrous and non-ferrous metals

The product name in an order: Hydraulic oil LUKOIL GEYSER MM 60 (SAE 60), TU 0253-013-79345251-2008

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	GOST 18995.1	894.7
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	23.3
Viscosity index	ASTM D2270	94
Total Base Number, mg KOH/1 g oil	ASTM D2896	3.8
Flash Point, COC, °C	ASTM D92	278
Pour Point, °C	GOST 20287 B	-19