

LUKOIL VERSO 10W-30

Universal Tractor Transmission Oil (UTTO)

Specifications

- Massey Ferguson CMS M1145
- API GL-4
- Massey Ferguson CMS M1135/M1143
- Sauer Sunstrand/Danfoss Hydro Static
- CNH MAT 3525
- KUBOTA UDT
- Valtra G2-08
- Ford ESN-M2C86-A
- White Q-1705/1722/1766/1766B/1802/1826
- JCMAS HK P-041
- Eaton Vickers E-FDGN-TB002-E
- Allison C-4
- Caterpillar TO-2
- Fiat AF 87
- CASE MS 1204/1206/1207/1209
- Ford ESN-M2C134-D/ESN-M2C86-B
- NH 410B/420A
- John Deere JDM J20C
- I.H.C. B5 & B6 Hydran
- Oliver Type 55/Type5J/Q1802
- Denison HF-0/HF-1/HF-2

Product description

Universal Tractor Transmission Oil (UTTO) specially formulated to provide the best lubrication for transmissions of combined hydraulic-transmission-wet braking systems in agricultural equipment.

Application

Recommended for use in transmissions, hydraulic and oil-immersed brakes, other ancillary systems fitted to tractors and agricultural machinery of world leading manufacturers.

Benefits

RELIABILITY

Extended and reliable operation of transmission systems under high loads and within wide temperature range

EXCEPTIONAL OXIDATION STABILITY

Extends life and performance even under some of the harshest conditions

SMOOTH OPERATIONS

Provides smooth operation of oil-immersed brakes, low noise and vibration levels

The product name in an order: Universal tractor oil LUKOIL VERSO SAE 10W-30, STO 79345251-022-2009

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D4052	867
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	9.9
Flash Point, COC, °C	ASTM D92	232
Viscosity index	ASTM D2270	139
Brookfield viscosity at -35 °C, mPa·s	ASTM D2983	34,067
Pour Point, °C	GOST 20287 B	-37