

LUKOIL VERSO MOTOR 10W-30

Super tractor universal oil (STOU)

Specifications

- API CD/SF
- ACEA E3
- API CG-4/CF-4
- Caterpillar TO-2
- FORD NEW HOLLAND 82009201/82009202
- MAN 271
- Sperry Vickers/Eaton M29503/I-280-S
- Ford WSS-M2C-159-B/C
- API CE/SF
- Allison C-4
- API GL-4
- FORD NEW HOLLAND 82009203
- John Deere J27
- Massey Ferguson CMS M1139/M1144/M1145
- ZF TE-ML 06B/07B
- Ford WSS-M2C86-B

Product description

Universal highly effective oil for year-round use in all systems agricultural equipment. Has excellent thermal and oxidation stability and improved detergent-dispersing properties.

Application

Recommended for use in engines, hydraulics and gearboxes with wet brakes, power steering in trucks and agricultural equipment a STOU-fluid is required.

Benefits

ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

OXIDATION RESISTANCE

High thermal and oxidation stability

MAXIMUM PROTECTION

Excellent lubricating properties provide reliable protection of friction units against wear and prevent metal fatigue.

The product name in an order: Universal tractor oil LUKOIL VERSO MOTOR SAE 10W-30, CTO 79345251-022-2009

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D1298 / ASTM D4052	859.1
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.4
Dynamic viscosity (CCS) at -25°C, mPa·s	ASTM D5293 / GOST R 52559	4,728
Borderline Pumping Viscosity (MRV) at -30 °C, mPa·s	ASTM D4684 / GOST R 52257	19,581
Viscosity index	ASTM D2270	149
Pour Point, °C	GOST 20287 B	-41
Flash Point, COC, °C	ASTM D92	222