

LUKOIL VERSO MOTOR 10W-40

Super tractor universal oil (STOU)

Specifications

- ZF TE-ML 06B/06F/07B
- Allison C-4
- API CG-4/SF
- Ford M2C 159B/159C
- Massey Ferguson CMS M1139/CMS M1144/CMS M1145
- ZF TE-ML 06A/06C/06Q/06R
- ACEA E2
- API GL-4
- Caterpillar TO-2
- John Deere J27
- MB 227.1/228.1

Product description

Universal highly effective oil for year-round use in all systems agricultural equipment. Has excellent thermal and oxidation stability and improved detergent-dispersing properties.

Application

Recommended for use in engines, hydraulics and gearboxes with wet brakes, power steering in trucks and agricultural equipment a STOU-fluid is specified.

Benefits

ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

OXIDATION RESISTANCE

High thermal and oxidation stability

MAXIMUM PROTECTION

Excellent lubricating properties provide reliable protection of friction units against wear and prevent metal fatigue.

LOW CONSUMPTION

Has low evaporation which reduces oil consumption during operation

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Sulphated ash, %	DIN 51575	872
Flash Point, COC, °C	ISO 2592	217
Kinematic viscosity at 40 °C, mm ² /s	DIN 51562/T1	90.74
Kinematic viscosity at 100 °C, mm ² /s	DIN 51562/T1	13.94
Pour Point, °C	ISO 3016	-42