

LUKOIL VERSO MOTOR 15W-40

Super tractor universal oil (STOU)

Specifications

- Massey Ferguson CMS M1145
- API CD/CE/CF
- API SE/SF
- AFNOR NF E 68603 (E)
- Fiat AF 87
- John Deere J27
- NH 024C/82009203
- Sauer Sunstrand/Danfoss Hydro Static
- API GL-4
- API CG-4/CF-4
- Allison C-4
- Eaton Vickers E-FDGN-TB002-E
- Ford M2C 159B/C
- Massey Ferguson CMS M1144
- ZF TE-ML 06B/07B/07D

Product description

Universal highly effective oil for year-round use in all systems agricultural equipment. Has excellent thermal and oxidation stability and improved detergent-dispersing properties.

Application

Recommended for use in engines, hydraulics and gearboxes with wet brakes, power steering in trucks and agricultural equipment a STOU-fluid is required.

Benefits

ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

OXIDATION RESISTANCE

High thermal and oxidation stability

MAXIMUM PROTECTION

Excellent lubricating properties provide reliable protection of friction units against wear and prevent metal fatigue.

LOW CONSUMPTION

Has low evaporation which reduces oil consumption during operation

The product name in an order: Universal tractor oil LUKOIL VERSO MOTOR SAE 15W-40, STO 79345251-022-2009

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D1298 / ASTM D4052	870
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	3,473
Pumping Viscosity at -25°C (MRV), mPa·s	ASTM D4684 / GOST R 52257	10,700
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.09
Pour Point, °C	GOST 20287 B	<-30
Flash Point, COC, °C	ASTM D92	234