

LUKOIL ATF IIIH

Automatic transmission fluid

Specifications

- GM Dexron IIIH/IIIG/IID
- ZF TE-ML 05L/09L/21L
- Ford WSS-M2C-138CJ/WSS-M2C-166H
- Caterpillar TO-2
- Volkswagen/Audi G 052 162
- RBAS TE-ML 09
- Ford Mercon
- Allison C-4/TES-389B
- Sperry Vickers/Eaton M2950S

Product description

Universal transmission fluid, developed for use in automatic gearboxes of passenger cars, trucks and mobile equipments.

Application

Designed for use in step-type automatic transmissions where GM Dexron® IIIH, IIIG or IID performance level is required. It can also be used as a power steering fluid.

Benefits

STABLE FRICTION PROPERTIES

Smooth speed shifting during the whole drain interval

YEAR-ROUND OPERATION

Low temperature dependence of viscosity (high viscosity index) and good low temperature properties

OXIDATION RESISTANCE

Provides stable properties during whole period of operation

The product name in an order: Automatic transmission fluid LUKOIL ATF IIIH, STO 79345251-247-2020

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Appearance	–	Transparent red liquid
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	7.9
Viscosity index	ASTM D2270	187
Dynamic viscosity at -40 °C, mPa·s	ASTM D2983	16,500
Flash Point, COC, °C	ASTM D92	231
Pour Point, °C	GOST 20287 B	-45
Density at 20 °C, kg/m ³	ASTM D4052	843.0