

LUKOIL MOTO 2T

Two-stroke small engine oil

Specifications

- HUTER
- JASO FB
- API TC
- ISO L-EGB

Product description

High-quality mineral oil intended for use in two-stroke gasoline engines of motorcycles, scooters, mopeds, etc. Formulated with high-quality base oil and highly effective modern low-ash additive package, which provides maximum engine protection in all operating conditions and significantly decreases risk of sludge and deposits formation in outlet system.

Application

Recommended for using in modern two-stroke engines of motorcycles, mopeds and scooters.

Proportion of the mixing must meet to the Operation and maintenance manual, but normally it is fuel:oil = 50:1

The product name in an order: Motor oil for two-stroke gasoline engines LUKOIL MOTO 2T, STO 79345251-002-2008

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	886
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	8.5
Viscosity index	ASTM D2270	96
Total Base Number, mg KOH/1 g oil	ASTM D2896	0.7
Sulphated ash, %	ASTM D874	0.05
Flash Point, COC, °C	ASTM D92	256
Pour Point, °C	GOST 20287 B	-22