

## LUKOIL GARDEN 2T

Mineral oil for two-stroke engines of garden equipment

### Specifications

- API TC
- ISO L-EGB
- JASO FB

### Product description

Modern mineral oil intended for use as a component of a fuel-oil mixture of small two-stroke gasoline engines in garden equipment. It has good detergent, lubricating and antiwear properties, which guarantee excellent engine performance under any conditions of operation.

### Application

Recommended for use in modern two-stroke engines of garden tools and garden equipment: lawn mowers, chainsaws, motor cultivators, walk-behind tractors, trimmers, etc.

Proportion of the mixing must meet to the Operation and maintenance manual, but normally it is fuel:oil = 50:1

The product name in an order: Motor oil LUKOIL GARDEN 2T, STO 79345251-095-2016

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	8.4
Viscosity index	ASTM D2270	95
Total Base Number, mg KOH/1 g oil	ASTM D2896	0.8
Sulphated ash, %	ASTM D874	0.05
Flash Point, COC, °C	ASTM D92	257
Pour Point, °C	GOST 20287 B	-22
Density at 20 °C, kg/m <sup>3</sup>	ASTM D4052	886