

LUKOIL SNOW 2T

Two-stroke engine oil for snowmobiles

Specifications

- API TC
- ISO L-EGD/GD++
- JASO FD
- Rotax 253

Product description

Synthetic motor oil for two-stroke engines of snowmobiles, UTVs and ATVs operating in cold climates. Polyisobutylene as a part of the oil minimizes smokiness and contributes to the formation of a stable mixture of fuel and oil, balanced additive package in combination with esters ensure perfect engine cleanliness and excellent wear protection.

Application

Recommended for forced two-stroke engines with mixed and separate lubrication systems. Provides high level of combustion and low pour point, which ensures reliable engine cold-start.

Benefits

EASY COLD START

Excellent low temperature capabilities provide quick cold start at low temperatures

ENGINE CLEANLINESS

High detergent and dispersant properties ensure clean valves and combustion chambers

SMOKELESS COMBUSTION

Polyisobutylene provides smokeless combustion

RELIABILITY

Resistance to high speed and overheating

The product name in an order: Two-stroke engine oil LUKOIL SNOW 2T, STO 79345251-162-2018

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D4052	854.0
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	7.9
Viscosity index	ASTM D2270	146
Total Base Number, mg KOH/1 g oil	ASTM D2896	2.0
Flash Point, COC, °C	ASTM D92	170
Pour Point, °C	GOST 20287 B	-42
Sulphated ash, %	ASTM D874	0.16
Appearance	-	clear homogeneous blue liquid