

LUKOIL GARDEN 4T 30

Four-stroke small engine oil for garden equipment

Specifications

- API SG

Product description

Modern mineral oil, designed for four-stroke gasoline small engines of garden and agricultural equipment. Formulated with high-quality base stocks and highly effective additive package.

Application

Recommended for modern 4-Stroke engines lawn mowers, cultivators, tillers, generators, mini tractors and other garden and agricultural equipment, where API SG oils are recommended.

Benefits

ENGINE CLEANLINESS

The optimum level of sulfate ash provides a low level of deposits in the engine

MAXIMUM PROTECTION

Excellent extreme pressure and anti-wear properties

The product name in an order: Motor oil LUKOIL GARDEN 4T SAE 30, STO 79345251-095-2016

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

| Property | Test methods | Value |
|---|--------------|-------|
| Kinematic viscosity at 100 °C, mm ² /s | ASTM D445 | 10.7 |
| Viscosity index | ASTM D2270 | 106 |
| Flash Point, COC, °C | ASTM D92 | 234 |
| Pour Point, °C | GOST 20287 B | -25 |
| Total Base Number, mg KOH/1 g oil | ASTM D2896 | 5.5 |
| Sulphated ash, % | ASTM D874 | 0.77 |
| Density at 20 °C, kg/m ³ | ASTM D4052 | 882 |