

LUKOIL LAYER 135

Formwork oil

Product description

Formwork oil that facilitates the removal of concrete products from molds. Provides excellent lubrication performance and corrosion protection. The oil has increased adhesion with formwork and mold materials to form a reliable lubricating film.

Application

Intended for use in production of heavy-weight concrete and monolithic construction. Recommended to overall spreaded by brush, roller, broom or sprayer in a thin layer avoiding oil puddles forming. To facilitate production and optimize oil consumption while spraying preliminary heating of the oil up to +50 °C - +60 °C is recommended.

The product name in an order: Form oil LUKOIL LAYER 135, STO 79345251-081-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D1298 / ASTM D4052	883
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	134
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.7
Flash Point, COC, °C	ASTM D92	235
Pour Point, °C	GOST 20287 B	<-20
Anti-corrosion properties (corrosion of the steel rod)	GOST 19199	Pass