

LUKOIL DIESEL M-10G2k

Seasonal engine oil for diesel engines

Meets requirements

API CC

Product description

It is mineral engine oil designed for winter operation of autotractor diesel engines naturally aspirated or turbocharged. Based on high-quality base oils and optimized additive package.

LUKOIL DIESEL M-10G2k is modification of M-10G2 with effective additive composition, which provides an increased drain interval.

Application

LUKOIL DIESEL M-10G2k is recommended for high-power naturally aspirated or turbocharged diesel engines of automotive vehicles and tractors. It is also effectively used in engines by KAMAZ, ZIL and other manufacturers where "G2k" oils are required.

The product name in an order: Engine oil LUKOIL DIESEL M-10G2k, STO 79345251-001-2007

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm2/s	ASTM D445	10.8
Viscosity index	ASTM D2270	104
Pour Point, °C	GOST 20287 B	-15
Total Base Number, mg KOH/1 g oil	ASTM D2896	7.1
Sulphated ash, %	ASTM D874	1.03
Flash Point, COC, °C	ASTM D92	235



Tel.: (495) 627-40-20

Fax.: (495) 981-76-84