

LUKOIL VERSO PLUS

Universal Tractor Transmission Oil (UTTO)

Specifications

- Massey Ferguson CMS M1145
- Allison C-4
- VCE WB101
- CASE MS 1207
- FORD NEW HOLLAND FNHA-2-C-201.00
- CASE MS 1206/1209
- CLAAS
- ZF TE-ML 03E/05F/17E/21F
- Caterpillar TO-2
- CNH MAT 3525/3505
- Ford ESN-M2C134-D
- John Deere JDM J20C
- Massey Ferguson CMS M1135/M1143

Product description

Universal Tractor Transmission Oil with an extended drain interval, specially designed to provide the best lubrication of transmissions, hydraulic, oil-immersion brakes and other systems of agricultural machinery.

Application

Recommended for use in hydraulic and hydrostatic systems, gearboxes and transmissions and oil-immersed brakes and other ancillary systems fitted to tractors and agricultural machinery, with both common and separate oil tanks.

Benefits

LONG SERVICE LIFE

Prevents deposit formation and provides extended drain interval due to high total base number

SMOOTH OPERATIONS

Provides smooth operation of oil-immersed brakes, low noise and vibration levels

RELIABILITY

Extended and reliable operation of transmission systems under high loads and within wide temperature range

EXCEPTIONAL OXIDATION STABILITY

Extends life and performance even under some of the harshest conditions

The product name in an order: Universal tractor oil LUKOIL VERSO PLUS, STO 79345251-022-2009

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D4052	872.1
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.5
Viscosity index	ASTM D2270	162
Flash Point, COC, °C	ASTM D92	210
Brookfield viscosity at -35 °C, mPa·s	ASTM D2983	31,217
Pour Point, °C	GOST 20287 B	-42