

## Teboil EP 80W-90

### PRODUCT DESCRIPTION

Teboil EP 80W-90 is a conventional mineral oil-based GL-4 grade transmission oil for both light and heavy-duty vehicles. It is suitable for use in most vehicles with manual transmissions that require the use of oil of this viscosity and grade.

### USE, BENEFITS AND FEATURES

- Effective pressure-resistant material reliably protects the transmission from wear in varying and demanding driving conditions.
- Low foaming tendency
- Balanced viscosity properties effectively lubricate at varying loads

### SPECIFICATIONS

- API GL-4
- MIL-L-2105
- MB 235.1
- MAN 341 Type E-1
- ZF TE-ML 06L, 08, 16A, 17A, 19A

### TYPICAL CHARACTERISTICS

Teboil EP	80W-90	Unit	Method
Density 20°C	885	kg/m <sup>3</sup>	ASTM D 4052
Viscosity 40 °C	133	mm <sup>2</sup> /s	ASTM D 445
Viscosity 100°C	15.0	mm <sup>2</sup> /s	ASTM D 445
Viscosity -26 °C	100,000	mPa.s	ASTM D 2983-87
Viscosity index	115		ASTM D 2270
Flash point	200	°C	ASTM D 92
Pour point	-33	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package. STORAGING: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

**Technical support**  
+358 (0)20 4700 916  
[lubricants@teboil.fi](mailto:lubricants@teboil.fi)

**Internet pages**  
[www.teboil.fi](http://www.teboil.fi)

**Postal address**  
Oy Teboil Ab  
PL 57  
01511 Vantaa



**TEBOIL**  
Lubricants