

TEBOIL 2T MIX

PRODUCT DESCRIPTION

High-quality mineral oil intended for use in two-stroke gasoline engines of motorcycles, scooters, mopeds, etc.

APPLICATIONS AND BENEFITS

- Recommended for using in modern two-stroke engines of motorcycles, mopeds, scooters, chainsaw and snowmobiles.
- Proportion of the mixing must meet to the Operation and maintenance manual, but normally it is fuel:oil = 50:1
- Forms a stable fuel-oil mixture over a wide temperature range

SPECIFICATIONS

- API TC

TYPICAL TEST DATA

TEBOIL 2T MIX	Value	Unit	Test method
Density at 20 °C	870	kg/m ³	ASTM D 4052
Kinematic viscosity at 100 °C	6,0	mm ² /s	ASTM D 445
Viscosity index	134	-	ASTM D 2270
Flash point	110	°C	ASTM D 92
Pour point	-45	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package. STORAGE: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

