

TEBOIL 2T SNOW

PRODUCT DESCRIPTION

Fully synthetic two-stroke engine oil for snowmobiles

APPLICATIONS AND BENEFITS

- Recommended for forced two-stroke engines with mixed and separate lubrication systems.
- Proportion of the mixing must meet to the Operation and maintenance manual, but normally it is fuel:oil = 50:1
- Formulated with high-quality base oil and highly effective modern low-ash additive package, which provides maximum engine protection in all operating conditions, significantly decreases risk of sludge, and deposits formation in outlet system.

SPECIFICATIONS

- API TC
- JASO FD
- ISO-L-EGD/ GD++
- Rotax 253

TYPICAL TEST DATA

TEBOIL 2T SNOW	Value	Unit	Test method
Density at 20 °C	855	kg/m ³	ASTM D 4052
Kinematic viscosity at 100 °C	7,3	mm ² /c	ASTM D 445
Viscosity index	145	-	ASTM D 2270
Flash point	165	°C	ASTM D 92
Pour point	-50	°C	ASTM D 97
Sulphated ash	0,15	%	ASTM D 874

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package.
STORAGING: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

