

## Teboil 2T Special Motorboat

### PRODUCT DESCRIPTION

Fully synthetic 2-stroke small engine oil for outboards

### APPLICATIONS AND BENEFITS

- Recommended for lubrication with oil-fuel mixture and for separate lubrication in modern two-stroke highly accelerated engines with water or air-cooling of boats, yachts, jet skis and motor boats in both fixed and suspendable version.
- Proportion of the mixing must meet to the Operation and maintenance manual.

### SPECIFICATIONS

- API TD
- NMMA TC-W3

### TYPICAL TEST DATA

Teboil 2T Special Motorboat	Value	Unit	Test method
Density at 20 °C	871	kg/m <sup>3</sup>	ASTM D 4052
Kinematic viscosity at 100 °C	6,5	mm <sup>2</sup> /s	ASTM D 445
Kinematic viscosity at 40 °C C	37	mm <sup>2</sup> /s	ASTM D 445
Viscosity index	128	-	ASTM D 2270
Flash point	110	°C	ASTM D 92
Pour point	-39	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package. STORAGE: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

