

TEBOIL 4T SPECIAL MOTORBOAT

PRODUCT DESCRIPTION

Special motor oil for four-stroke gasoline engines of watercrafts

APPLICATIONS AND BENEFITS

- Recommended for use in four-stroke gasoline and diesel outboard engines of various types
- Provides improved lubricating, anticorrosive and antioxidant properties.
- Provides increased protection of boat engines and other types of water transport

SPECIFICATIONS

- API SL/CF
- NMMA FC-W

TYPICAL TEST DATA

TEBOIL 4T SPECIAL MOTORBOAT	Value	Unit	Test method
Viscosity grade	10W-40	-	-
Density at 20 °C	872	kg/m3	ASTM D 4052
Kinematic viscosity at 100 °C	13,9	mm2/s	ASTM D 445
Viscosity index	148	-	ASTM D 2270
Flash point	224	°C	ASTM D 92
Pour point	-42	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package. STORAGING: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

