

Teboil EP 75W-90

PRODUCT DESCRIPTION

Teboil EP 75W-90 is a fully synthetic mineral oil-based GL-4 grade transmission oil for both light and heavy-duty vehicles. Due to its fully synthetic base oil, it reduces transmission power loss and helps reduce fuel consumption.

USE, BENEFITS AND FEATURES

- Effective pressure-resistant material reliably protects the transmission from wear in varying and demanding driving conditions.
- Low pour point ensures smooth operation of the transmission even in extremely low temperatures
- Balanced viscosity properties effectively lubricate at varying loads
- Helps reduce fuel consumption

SPECIFICATIONS

- API GL-4, MT-1
- MIL-L-2105
- ZF TE-ML 08

TYPICAL CHARACTERISTICS

Teboil EP	75W-90	Unit	Method
Density 20°C	858	kg/m ³	ASTM D 4052
Viscosity 40 °C	83	mm ² /s	ASTM D 445
Viscosity 100°C	14.0	mm ² /s	ASTM D 445
Viscosity -40 °C	30,000	mPa.s	ASTM D 2983-87
Viscosity index	174		ASTM D 2270
Flash point	180	°C	ASTM D 92
Pour point	-48	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package.
STORAGING: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

Technical support
+358 (0)20 4700 916
lubricants@teboil.fi

Internet pages
www.teboil.fi

Postal address
Oy Teboil Ab
PL 57
01511 Vantaa



TEBOIL
Lubricants