

Teboil Fluid E

PRODUCT DESCRIPTION

High quality semi-synthetic automatic transmission fluid of passenger cars and commercial vehicles. It can also be used as a power steering fluid.

APPLICATIONS AND BENEFITS

Provides excellent thermal oxidative stability and maintains all properties even in the event of extended drain intervals. Provides consistent and smooth operation of many automotive transmission systems.

SPECIFICATIONS

- GM Dexron IIIH
- Ford Mercon
- Allison C4, TES-389
- MAN 339 Type Z1/ V1
- MAN 339 Type L1/ L2
- Volvo 97341
- Voith 55.6335
- CAT TO-2
- ZF TE-ML 02F/03D/04D/05L/09/11B/14A/17C/21L

TYPICAL TEST DATA

Teboil Fluid E	Value	Unit	Test method
Density at 20 °C	846	kg/m ³	ASTM D 4052
Kinematic viscosity at 100 °C	8,0	mm ² /s	ASTM D 445
Viscosity index	190	-	ASTM D 2270
Flash point	220	°C	ASTM D 92
Dynamic viscosity at -40 °C	16 000	mPa·s	ASTM D 2983
Pour point	-48	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package. STORAGING: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

