

LUKOIL TRANSMISSION TM-5 85W-140

High quality API GL-5 axle oil

Specifications

- API GL-5

Product description

Multi-grade mineral axle oil for passenger cars, commercial vehicles and other mobile equipment where API GL-5 oils are recommended. The product is based on highly refined mineral oils blended with efficient additive package, providing excellent antiwear and EP properties.

Application

Recommended for use in heavy-duty axles, final drives of off-road equipment (including construction, mining, agricultural), as well as light and heavy-duty trucks and cars, requiring the use of oils with API GL-5 properties and SAE 85W-140 viscosity grade

Benefits

EXCELLENT ANTI-FOAMING PROPERTIES

Provides stable oil bearing capacity and prevents accelerated oil oxidation

RELIABLE PROTECTION

High oil film thickness over entire drain interval

OXIDATION RESISTANCE

Provides stable properties during whole period of operation

The product name in an order: Oil LUKOIL TRANSMISSION TM-5 SAE 85W-140, API GL-5, STO 00044434-009-2006

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

| Property | Test methods | Value |
|---|--------------|--------|
| Kinematic viscosity at 100 °C, mm ² /s | ASTM D445 | 26.3 |
| Brookfield viscosity at -12 °C, mPa·s | ASTM D2983 | 44,852 |
| Viscosity index | ASTM D2270 | 98 |
| Flash Point, COC, °C | ASTM D92 | 227 |
| Pour Point, °C | GOST 20287 B | -22 |