

LUKOIL GENESIS SPECIAL A5L 0W-30

Fully synthetic motor oil

Specifications

- API SL/CF
- ACEA A1/B1, A5/B5

Product description

Fully synthetic engine oil for modern gasoline and diesel engines of passenger cars (both non-charged and turbocharged) which are maintained at service stations. Formulated with high-quality synthetic base oils in combination with advanced additives technology.

Application

Recommended for use in gasoline and diesel engines (without DPF) of passenger cars. The product is recommended for Volvo and Toyota engines, which require oils with ACEA A5/B5 performance level and SAE 0W-30 viscosity grade, and other OEMs, which require API SL/CF or ACEA A5/B5 oil performance level. Suitable for use in gasoline Renault engines without DPF.

Benefits

EASY START

Guarantees easy engine start at low temperatures due to excellent low-temperature properties

FUEL ECONOMY

Superior fuel economy thanks to lower HTHS viscosity and potential to reduce emissions

OXIDATION RESISTANCE

High thermal and oxidation stability

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL A5L 0W-30, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D1298 / ASTM D4052	843.8
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.87
Viscosity index	ASTM D2270	182
Dynamic viscosity (CCS) at -35°C, mPa·s	ASTM D5293 / GOST R 52559	4,850
Total Base Number, mg KOH/1 g oil	ASTM D2896	11.6
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12.48
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-43