

LUKOIL GENESIS SPECIAL A5L 5W-30

Fully synthetic motor oil

Specifications

- API SL/CF
- ACEA A1/B1, A5/B5

Product description

Fully synthetic engine oil for modern gasoline and diesel engines of passenger cars (both non-charged and turbocharged) which are maintained at service stations. Formulated with high-quality synthetic base oils in combination with advanced additives technology.

Application

Recommended for use in gasoline and diesel engines (without DPF) of passenger cars. The product is recommended for both gasoline and diesel (without DPF) engines of Ford, Renault (gasoline engines only), Kia, Hyundai, Toyota, Mitsubishi and other vehicles, which require API SL and/or ACEA A1/B1, A5/B5 performance level and SAE 5W-30 viscosity grade.

Benefits

EASY COLD START

Synthetic base oil provides easy cold start-up

FUEL ECONOMY

Superior fuel economy thanks to lower HTHS viscosity and potential to reduce emissions

OXIDATION RESISTANCE

Excellent anti-oxidation and anticorrosion properties

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL A5L 5W-30, STO 97345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D1298 / ASTM D4052	850.2
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.25
Viscosity index	ASTM D2270	162
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	4,230
Total Base Number, mg KOH/1 g oil	ASTM D2896	11.1
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	10.3
Flash Point, COC, °C	ASTM D92	235
Pour Point, °C	GOST 20287 B	-45