

## LUKOIL GENESIS SPECIAL A3L 10W-40

Synthetic technology engine oil

### Specifications

- API SN/CF
- ACEA A3/B3, A3/B4

### Product description

Synthetic technology-based engine oil for gasoline and diesel engines without aftertreatment devices which are maintained at service stations. Formulated with high-quality synthetic base oils in combination with advanced additives technology.

### Application

Recommended for use in gasoline and diesel engines of cars such as Renault, Mercedes-Benz, Volkswagen, Audi, Skoda, Kia, Hyundai, Toyota, Mitsubishi, Peugeot, Citroen and other manufacturers, which require API SN and/or ACEA A3/B3, A3/B4 performance levels and SAE 10W-40 viscosity grade.

### Benefits

#### MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

#### LONG SERVICE LIFE

Specially selected additives help to improve oil life under severe operating conditions

#### OXIDATION RESISTANCE

Excellent anti-oxidation and anticorrosion properties

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL A3L 10W-40, STO 79345251-074-2015

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	854.4
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	13.6
Viscosity index	ASTM D2270	155
Dynamic viscosity (CCS) at -25°C, mPa·s	ASTM D5293 / GOST R 52559	4,600
Total Base Number, mg KOH/1 g oil	ASTM D2896	11.15
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	8.9
Flash Point, COC, °C	ASTM D92	220
Pour Point, °C	GOST 20287 B	-45