

## LUKOIL GENESIS SPECIAL A3L 5W-40

Fully synthetic motor oil

### Specifications

- API SN/CF
- ACEA A3/B3, A3/B4

### Product description

Fully synthetic engine oil for modern gasoline and diesel engines of passenger cars (both non-charged and turbocharged) which are maintained at service stations. Formulated with high-quality synthetic base oils in combination with advanced additives technology.

### Application

Recommended for use in gasoline and diesel engines (without DPF) of passenger cars. The product is recommended for both gasoline and diesel (without DPF) engines of Renault, Mercedes-Benz, Volkswagen, Audi, Skoda, Kia, Hyundai, Toyota, Mitsubishi, Nissan, Peugeot, Citroen and other vehicles, which require API SN and/or ACEA A3/B3, A3/B4 performance level and SAE 5W-40 viscosity grade.

### Benefits

#### EASY COLD START

Synthetic base oil provides easy cold start-up

#### LONG SERVICE LIFE

Specially selected additives help to improve oil life under severe operating conditions

#### OXIDATION RESISTANCE

Excellent anti-oxidation and anticorrosion properties

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL A3L 5W-40, STO 79345251-074-2015

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	851
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	13.9
Viscosity index	ASTM D2270	175
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	5,374
Total Base Number, mg KOH/1 g oil	ASTM D2896	11.1
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	10
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-40