

LUKOIL LUXE SYNTHETIC 5W-30

Fully synthetic engine oil

Specifications

- API SL/CF
- Ford WSS-M2C-913-A/B/C/D
- IVECO 18-1811 Classe S1
- JSC «AVTOVAZ»
- ACEA A1/B1, A5/B5
- Renault RN 0700
- Fiat 9.55535-G1

Product description

Fully synthetic engine oil for modern gasoline and diesel engines of passenger cars. Formulated with high-quality synthetic base oils in combination with advanced additives technology.

Application

Recommended for all-season use in gasoline and diesel engines (without Diesel Particulate Filters) required engine oil with API SL and/or ACEA A1/B1, A5/B5 performance level and SAE 5W-30 viscosity.

Benefits

MAXIMUM PROTECTION

Provides excellent protection against wear in severe operating conditions

EXCELLENT CLEANLINESS

Prevents the formation of high and low temperature deposits on engine components

DEPOSITS PROTECTION

Keeps valves and pistons clean and protects the catalytic converter

The product name in an order: Multigrade Engine Oil LUKOIL LUXE Synthetic SAE 5W-30, API SL/CF, STO 00044434-003-2005

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D1298 / ASTM D4052	850
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.6
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	60.9
Viscosity index	ASTM D2270	165
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	4,941
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	20,100
Total Base Number, mg KOH/1 g oil	ASTM D2896	10.9
Sulphated ash, %	ASTM D874	1.2
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9.6
Flash Point, COC, °C	ASTM D92	235
Pour Point, °C	GOST 20287 B	-46