

## LUKOIL SUPER 20W-50

High-quality multigrade engine oil

### Specifications

- PJSC «ZMZ»
- API SG/CD
- JSC «AVTOVAZ»

### Product description

Mineral multigrade engine oil based on highly purified mineral base stocks, which provide reliable engine performance in a wide range of temperatures and loads.

### Application

It is recommended for use in gasoline and diesel engines of passenger cars and light commercial vehicles.

### Benefits

#### OXIDATION RESISTANCE

High thermal and oxidation stability

#### ENGINE CLEANLINESS

Protection against sludge and deposits

The product name in an order: Multigrade Engine Oil LUKOIL SUPER SAE 20W-50, API SG/CD, STO 00044434-001-2005

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	16.5
Viscosity index	ASTM D2270	138
Dynamic viscosity (CCS) at -15°C, mPa·s	ASTM D5293 / GOST R 52559	4,077
Dynamic viscosity (MRV) at -20 °C, mPa·s	ASTM D4684 / GOST R 52257	14,900
Total Base Number, mg KOH/1 g oil	ASTM D2896	6.5
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9.2
Flash Point, COC, °C	ASTM D92	236
Pour Point, °C	GOST 20287 B	-24