

LUKOIL SUPER 15W-40

High-quality multigrade engine oil

Specifications

- PJSC «ZMZ»
- API SG/CD
- JSC «AVTOVAZ»

Product description

Mineral multigrade engine oil based on highly purified mineral base stocks, which provide reliable engine performance in a wide range of temperatures and loads.

Application

It is recommended for use in gasoline and diesel engines of passenger cars and light commercial vehicles.

Benefits

OXIDATION RESISTANCE

High thermal and oxidation stability

ENGINE CLEANLINESS

Protection against sludge and deposits

The product name in an order: Multigrade Engine Oil LUKOIL SUPER SAE 15W-40, API SG/CD, STO 00044434-001-2005

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.4
Viscosity index	ASTM D2270	132
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	5,712
Pumping Viscosity at -25°C (MRV), mPa·s	ASTM D4684 / GOST R 52257	21,200
Total Base Number, mg KOH/1 g oil	GOST 11362	8.4
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	8.9
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-31