

LUKOIL LUXE TURBO DIESEL 10W-40

High quality multigrade engine oil

Specifications

- API CF

Product description

High-quality semi-synthetic multigrade engine oil. Produced using a highly effective synthetic and mineral base oils with additive package.

Application

Intended for use in diesel engines of passenger cars, vans and light duty trucks, both non-charged and turbo-charged.

Benefits

EASY COLD START

Provides easy cold start at low temperatures

OXIDATION RESISTANCE

Excellent resistance to oxidation and corrosion

EXCELLENT CLEANLINESS

Prevents the formation of high and low temperature deposits on engine components

The product name in an order: Multigrade Semi-synthetic engine oil LUKOIL LUXE TURBO DIESEL SAE 10W-40, API CF, STO 00044434-003-2005

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	874
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.9
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	93.5
Viscosity index	ASTM D2270	154
Dynamic viscosity (CCS) at -25°C, mPa·s	ASTM D5293 / GOST R 52559	5,390
Borderline Pumping Viscosity (MRV) at -30 °C, mPa·s	ASTM D4684 / GOST R 52257	26,600
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.0
Sulphated ash, %	ASTM D874	1.0
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	11
Flash Point, COC, °C	ASTM D92	225
Pour Point, °C	GOST 20287 B	-33