

## LUKOIL LUXE 15W-40

### Semi-synthetic engine oil

#### Specifications

- PJSC «ZMZ»
- API SL/CF
- JSC «AVTOVAZ»

#### Product description

High-quality semi-synthetic engine oil. Produced using a highly effective additive package of foreign production.

#### Application

Intended for use in gasoline and diesel engines of passenger cars, vans and light trucks, where API SL/CF performance level is required.

#### Benefits

##### OXIDATION RESISTANCE

Excellent resistance to oxidation and corrosion

##### ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

The product name in an order: Multigrade Engine Oil LUKOIL LUXE semi-synthetic SAE 15W-40, API SL/CF, STO 00044434-003-2005

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	867
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	13.4
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	91.5
Borderline Pumping Viscosity (MRV) at -30 °C, mPa·s	ASTM D4684 / GOST R 52257	24,475
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	5,596
Viscosity index	ASTM D2270	147
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	11
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.3
Flash Point, COC, °C	ASTM D92	221
Pour Point, °C	GOST 20287 B	-29