

# LUKOIL LUXE 10W-40

## Semi-synthetic engine oil

### Approvals

- PJSC «ZMZ»
- JSC «UMZ»
- JSC «AVTOVAZ»

### Meets requirements

- API SL/CF

### Product description

High-quality semi-synthetic engine oil. Produced using a highly effective additive package of foreign production.

### Application

Intended for use in gasoline and diesel engines of passenger cars, vans and light trucks, where API SL/CF performance level is required.

### Benefits

#### OXIDATION RESISTANCE

Excellent resistance to oxidation and corrosion

#### ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

The product name in an order: Multigrade Engine Oil LUKOIL LUXE semi-synthetic SAE 10W-40, API SL/CF, STO 00044434-003-2005

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	873
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	14.2
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	95
Viscosity index	ASTM D2270	157
Dynamic viscosity (CCS) at -25°C, mPa·s	ASTM D5293 / GOST R 52559	5,300
Borderline Pumping Viscosity (MRV) at -30 °C, mPa·s	ASTM D4684 / GOST R 52257	32,033
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12
Flash Point, COC, °C	ASTM D92	223
Pour Point, °C	GOST 20287 B	-34