

LUKOIL LUXE 10W-30

Semi-synthetic engine oil

Approvals

- PJSC «ZMZ»

Meets requirements

- JSC «AVTOVAZ»
- API SL/CF

Product description

High-quality semi-synthetic engine oil. Produced using a highly effective additive package of foreign production.

Application

Intended for use in gasoline and diesel engines of passenger cars, vans and light trucks, where API SL/CF performance level is required.

Benefits

OXIDATION RESISTANCE

Excellent resistance to oxidation and corrosion

ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

The product name in an order: Multigrade Engine Oil LUKOIL LUXE semi-synthetic SAE 10W-30, API SL/CF, STO 00044434-003-2005

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m ³	ASTM D1298 / ASTM D4052	867
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.5
Viscosity index	ASTM D2270	145
Dynamic viscosity (CCS) at -25°C, mPa·s	ASTM D5293 / GOST R 52559	4,915
Borderline Pumping Viscosity (MRV) at -30 °C, mPa·s	ASTM D4684 / GOST R 52257	17,664
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.3
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12
Flash Point, COC, °C	ASTM D92	222
Pour Point, °C	GOST 20287 B	-35