

LUKOIL GENESIS SPECIAL ADVANCED 10W-40

Synthetic technology engine oil

Specifications

- API SN/CF
- VW 502 00/505 00
- Renault RN 0700/0710
- Fiat 9.55535-G2
- ACEA A3/B3, A3/B4
- MB 229.3
- PSA B71 2294/2300
- Opel GM-LL-A/B-025

Product description

Synthetic technology-based engine oil for gasoline and diesel engines without aftertreatment devices.

Application

Recommended for use in gasoline and diesel engines of cars such as Mercedes Benz, Volkswagen, Renault, KIA, Hyundai, Toyota, Nissan, Honda, Mitsubishi and other manufacturers, which require API SN performance levels and SAE 10W-40 viscosity.

Benefits

ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL ADVANCED 10W-40, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	860.6
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.9
Viscosity index	ASTM D2270	166
Dynamic viscosity (CCS) at -25 °C, mPa·s	ASTM D5293 / GOST R 52559	3,982
Borderline Pumping Viscosity (MRV) at -30 °C, mPa·s	ASTM D4684 / GOST R 52257	15,000
Total Base Number, mg KOH/1 g oil	ASTM D2896	10.6
Sulphated ash, %	ASTM D874	1.2
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9
Flash Point, COC, °C	ASTM D92	230
Pour Point, °C	GOST 20287 B	-41