

## LUKOIL GENESIS SPECIAL ADVANCED 5W-30

Synthetic technology engine oil

### Specifications

- API SL/CF
- Ford WSS-M2C-913-A/B/C/D
- Meets engine tests requirements API SN
- ACEA A1/B1, A5/B5
- Renault RN 0700

### Product description

Synthetic technology-based engine oil for gasoline and diesel engines without aftertreatment devices.

### Application

Developed for use in gasoline and diesel engines of modern cars. Recommended for use in Ford engines which require oils according to Ford WSS-M2C913-A/B/C/D specifications and SAE 5W-30 viscosity level and also in Kia, Hyundai, Toyota, Mazda и Nissan cars where ACEA A5/B5 and API SL/CF oils are required.

### Benefits

#### FUEL ECONOMY

Superior fuel economy thanks to lower HTHS viscosity and potential to reduce emissions

#### LONG SERVICE LIFE

Specially selected additives help to improve oil life under severe operating conditions

#### EASY START

Excellent low-temperature pumpability

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL ADVANCED 5W-30, STO 97345251-074-2015

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	9.4
Viscosity index	ASTM D2270	167
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	4,400
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	13,100
Total Base Number, mg KOH/1 g oil	ASTM D2896	10.7
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12.8
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-52