

## LUKOIL GENESIS SPECIAL 5W-40

Fully synthetic engine oil

### Specifications

- API SN/CF
- VW 502 00/505 00
- Renault RN 0700/0710
- Opel GM-LL-B-025
- BMW LL-01
- ACEA A3/B3, A3/B4
- MB 229.3/226.5/229.5
- Fiat 9.55535-N2/Z2
- PSA B71 2296
- Porsche A40

### Product description

Fully synthetic engine oil of the latest generation for engines of cars which are serviced at car maintenance centers. Developed with high quality synthetic base oils and advanced additive technology providing high level of stability against oxidation, wear and corrosion.

### Application

Intended for all-season usage in gasoline and diesel engines of VAG (Volkswagen, Audi, Skoda, Seat) and Daimler cars. Recommended in gasoline engines of Porsche cars, serviced at car maintenance and service stations over warranty and post-warranty periods of operation.

The oil is licensed by API according to SN specification and meets requirements of ACEA A3/B3, A3/B4 categories and SAE 5W-40 viscosity grade.

### Benefits

#### MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

#### OXIDATION RESISTANCE

Excellent anti-oxidation and anticorrosion properties

#### EXCELLENT CLEANLINESS

Prevents the formation of high and low temperature deposits on engine components

#### EASY COLD START

Provides easy cold start at low temperatures

The product name in an order: Motor Oil LUKOIL GENESIS SPECIAL 5W-40, STO 79345251-074-2015

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	851.6
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	13.34
Viscosity index	ASTM D2270	172
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	5,594
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	27,300
Total Base Number, mg KOH/1 g oil	ASTM D2896	10.16
Sulphated ash, %	ASTM D874	1.16
Flash Point, COC, °C	ASTM D92	226
Pour Point, °C	GOST 20287 B	-40