

# LUKOIL GENESIS SPECIAL A5/B5 5W-30

# Fully synthetic energy-conserving engine oil

## **Specifications**

- API SL/CF
- Ford WSS-M2C-913-A/B/C/D
- Jaguar Land Rover ST JLR.03.5003
- ACEA A5/B5, A1/B1
- Renault RN 0700
- IVECO 18-1811 Classe S1

## Product description

Multigrade fully synthetic engine oil of the latest generation, designed in accordance with modern requirements to fuel economy. Intended for use at service stations in all modern high-powered engines of passenger cars and light trucks (both non-charged and turbocharged), during the warranty and post-warranty period of operation.

## Application

Recommended for all-season use in gasoline and diesel engines with direct fuel injection, operating in harsh conditions with extended oil change intervals. Recommended for Ford and Renault which require WSS-M2C913-D and RN 0700 performance level, respectively.

#### **Benefits**

#### MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

#### **OXIDATION RESISTANCE**

Excellent resistance to oxidation and corrosion

#### **ENGINE CLEANLINESS**

Helps to reduce the formation of deposits and keeps the engine clean

#### **FUEL ECONOMY**

Superior fuel economy thanks to lower HTHS viscosity and potential to reduce emissions

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL A5/B5 5W-30, STO 79345251-074-2015

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by 000 «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m3	ASTM D1298 / ASTM D4052	847.6
Kinematic viscosity at 100 °C, mm2/s	ASTM D445	10
Viscosity index	ASTM D2270	174
Dynamic viscosity (CCS) at -30°C, mPa· s	ASTM D5293 / GOST R 52559	3,353
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	13,100
Total Base Number, mg KOH/1 g oil	ASTM D2896	9.4
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-40

Tel.: (495) 627-40-20

Fax.: (495) 981-76-84