

LUKOIL GENESIS SPECIAL 0W-40

Fully synthetic engine oil with improved low temperature performance

Specifications

- API SN/CF
- VW 502 00/505 00
- MB 229.5, 226.5, 229.3
- Porsche A40
- ACEA A3/B4, A3/B3
- Renault RN 0700/0710
- BMW LL-01
- Ford WSS-M2C-937-A

Product description

Synthetic engine oil with improved low temperature properties for gasoline and diesel engines of modern cars, light trucks and vans (without DPF). Recommended for car maintenance at service stations.

Application

Designed for all-season use in gasoline and diesel engines (without particulate filters) of VAG (Volkswagen, Audi, Skoda, Seat) and Daimler cars, as well as in Porsche gasoline engines, both during the warranty and post-warranty periods. The oil can also be used in engines requiring an API SN or ACEA A3/B4 oil in combination with a 0W-40 viscosity grade.

Benefits

EASY COLD START

Excellent low-temperature properties provide easy cold start

LOW CONSUMPTION

Poly-alpha-olefin base stock provides low oil consumption

OXIDATION RESISTANCE

Excellent anti-oxidation and anticorrosion properties

MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

The product name in an order: Engine Oil LUKOIL GENESIS SPECIAL 0W-40, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13
Viscosity index	ASTM D2270	183
Dynamic viscosity (CCS) at -35°C, mPa·s	ASTM D5293 / GOST R 52559	5,970
Borderline Pumping Viscosity (MRV) at -40 °C, mPa·s	ASTM D4684 / GOST R 52257	21,500
Total Base Number, mg KOH/1 g oil	ASTM D4739	10.19
Sulphated ash, %	ASTM D874	1.2
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9.7
Flash Point, COC, °C	ASTM D92	226
Pour Point, °C	GOST 20287 B	-54