

LUKOIL GENESIS SPECIAL 0W-30

Fully synthetic engine oil for extremely low temperatures

Specifications

- API SL/CF
- MB 229.5, 226.5, 229.3, 229.1
- VW 502 00/505 00
- ACEA A3/B3, A3/B4
- Renault RN 0700/0710
- VOLVO 95200356

Product description

Fully synthetic engine oil for extremely low temperatures for modern passenger cars, light trucks and vans without Diesel Particulate Filter (DPF). It is recommended for service maintenance at service stations.

Application

Based on PAO base stocks and advanced additive technology. The oil perfectly suits for regions with severe operating conditions including CIS countries.

LUKOIL GENESIS SPECIAL 0W-30 is a perfect solution for automobiles operating in regions with extremely low temperatures.

Benefits

EASY COLD START

Excellent low-temperature properties provide easy cold start

LOW CONSUMPTION

Poly-alpha-olefin base stock provides low oil consumption

OXIDATION RESISTANCE

Excellent anti-oxidation and anticorrosion properties

MAXIMUM PROTECTION

Maximum protection against wear at severe conditions of urban driving cycle

The product name in an order: Engine oil LUKOIL GENESIS SPECIAL 0W-30, STO 79345251-040-2010

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	845.2
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	12
Viscosity index	ASTM D2270	180
Dynamic viscosity (CCS) at -35°C, mPa·s	ASTM D5293 / GOST R 52559	5,921
Dynamic viscosity (MRV) at -40 °C, mPa·s	ASTM D4684 / GOST R 52257	21,000
Total Base Number, mg KOH/1 g oil	ASTM D2896	10.1
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	8.7
Flash Point, COC, °C	ASTM D92	224
Pour Point, °C	GOST 20287 B	-52