

LUKOIL STANDARD 20W-50

Multigrade mineral engine oil

Specifications

- API SF/CC

Product description

Multigrade engine oil for gasoline and diesel engines. This oil is intended for use in high-mileage classic cars which are characterized by excessive oil consumption.

Application

Suitable for use in passenger cars and light commercial vehicles.

Benefits

OXIDATION RESISTANCE

High thermal and oxidation stability

ENGINE CLEANLINESS

The optimum level of sulfate ash provides a low level of deposits in the engine

The product name in an order: Motor oil LUKOIL STANDARD SAE 20W-50, API SF/CC, STO 00044434-002-2005

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	891
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	18.3
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	155
Viscosity index	ASTM D2270	127
Dynamic viscosity (CCS) at -15°C, mPa·s	ASTM D5293 / GOST R 52559	5,921
Dynamic viscosity (MRV) at -20 °C, mPa·s	ASTM D4684 / GOST R 52257	21,300
Sulphated ash, %	ASTM D874	0.9
Flash Point, COC, °C	ASTM D92	239
Total Base Number, mg KOH/1 g oil	ASTM D2896	6.3
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	5
Pour Point, °C	GOST 20287 B	-22