

LUKOIL GENESIS ARMORTECH FD 5W-30

Multigrade fully synthetic engine oil for Ford engines

Specifications

- API SL/CF
- Ford WSS-M2C-913-A/B/C/D
- Fiat 9.55535-G1
- Jaguar Land Rover ST JLR.03.5003
- ACEA A1/B1, A5/B5
- Renault RN 0700
- IVECO 18-1811 Classe S1

Product description

Fully synthetic engine oil for modern gasoline and diesel engines developed by Ford (both non-charged and turbocharged). Formulated with DuraMax® innovative technology.

Application

Recommended for all-season use in gasoline and diesel engines (without Diesel Particulate Filter) of Ford, Jaguar, Land Rover and other cars (both during warranty and afterwarranty periods). The oil can also be used for in any other engines, which require API SN, ACEA A1/B1, A5/B5 performance level and SAE 5W-30 viscosity.

Benefits

ADVANCED FUEL ECONOMY

Excellent fuel economy due to optimal viscometric characteristics

OXIDATION RESISTANCE

Excellent anti-oxidation and anticorrosion properties

MAXIMUM PROTECTION

Adjusted for severe conditions of urban cycle

EASY COLD START

Excellent low-temperature properties

The product name in an order: Engine oil LUKOIL GENESIS ARMORTECH FD 5W-30, STO 79345251-185-2019

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	844.8
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.4
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	56.2
Viscosity index	ASTM D2270	177
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	3,059
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	13,108
Total Base Number, mg KOH/1 g oil	ASTM D2896	10
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-40