

# LUKOIL TRANSMISSION TM-4 SAE 80W-90, API GL-4

Series of high quality gear oils API GL-4 level performance

## **APPROVALS**

**JSC «AVTOVAZ»**

## **MEETS REQUIREMENTS**

**API** GL-4  
**MIL-L-2105**  
**ZF** TE-ML 08, 16A, 17A, 19A  
**MB** 235.1

## **PRODUCT DESCRIPTION**

**LUKOIL TRANSMISSION TM-4 SAE 80W-90, API GL-4** is a multi-grade mineral gear oil for manual transmissions of passenger cars, commercial and custom vehicles. It is manufactured using highly refined base oils blended with advanced high-performance additive package.

## **APPLICATION**

**LUKOIL TRANSMISSION TM-4 SAE 80W-90, API GL-4** is intended for use in manual transmissions of passenger cars or

commercial vehicles and torque dividers, power takes off boxes of mobile equipment, where API GL-4 level is required.

## **BENEFITS**

- Advanced level of extreme pressure properties and protection against wear
- Extended and reliable operation of transmission systems under high loads and over a wide temperature range
- Excellent oxidative and thermal stability
- Excellent anti-corrosion and anti-foam characteristics

The product name in an order:

Oil LUKOIL TRANSMISSION TM-4 SAE 80W-90, API GL-4, STO 00044434-009-2006

## **TYPICAL TEST DATA**

PROPERTY	Test method	LUKOIL TRANSMISSION TM-4, SAE 80W-90, API GL-4
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	GOST 33 / ASTM D445 / GOST R 53708	15.2
Brookfield viscosity at -26 °C, mPa·s	GOST 1929 / ASTM D2983	110,777
Viscosity Index	GOST 25371 / ASTM D2270	102
Flash Point, COC, °C	GOST 4333 / ASTM D92	218
Pour Point, °C	GOST 20287 B	-30

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to mak