

## LUKOIL ANTIFREEZE G11 GREEN

### Engine coolant

#### Meets requirements

- ASTM D3306
- GOST 28084-89
- MTU MTL 5048
- SAE J1034
- Ford ESD M97B49-A
- VW TL 774-C

#### Product description

High performance ready-mix engine coolant based on ethylene glycol and hybrid additives technology. The coolant contains organic acids salts and silicates which help to prevent corrosion process.

#### Application

Recommended for all-season use in closed cooling system of modern engines of vehicles operated at temperature not lower than – 40°C.

#### Benefits

##### EXTENDED DRAIN

Extends drain interval due to unique combination of corrosion inhibitors

##### RELIABLE PROTECTION

Reduces repair and maintenance costs of cooling systems

The product name in an order: Engine cooling fluid LUKOIL ANTIFREEZE G11 GREEN, STO 79345251-008-2008

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Color	GOST 28084	Green
Density at 20 °C, kg/m <sup>3</sup>	GOST 18995.1	1,080
Crystallization temperature, °C	GOST 28084	-41
Boiling temperature, °C	p.7.3 STO	110
pH at 20 °C	GOST 22567.5	8.2
Alkalinity, ml	GOST 28084	14.3