

## LUKOIL ANTIFREEZE HD

Premium coolant with low pour point

### Specifications

- MB 325.0
- Ford WSS-M97B51-A1
- Deutz-Fahr
- Huerlimann
- Same
- Chrysler MS-9769
- CUNA NS 956-16
- AFNOR NF R 15601
- AS 2108-2004
- BS 6580
- MTU MTL 5048
- JCB STD00088
- Lamborghini-Tractors
- Dodge
- John Deere JDM H24
- ASTM D3306/D6210
- SAE J1034
- SANS 1251:2005
- ONORM V5123
- SH 0521-1999

### Product description

High-quality ready-for-use coolant of premium level with low pour point. Formulated based on ethyleneglycol and hybrid anticorrosion additive package, which contains organic acid salts, nitrites and silicates. The product is free from amines and phosphates.

### Application

Recommended for use in closed cooling systems of modern engines of commercial vehicles, operated at ambient temperatures down to -41 °C.

### Benefits

#### EXTENDED DRAIN

Extends drain interval due to unique combination of corrosion inhibitors

#### RELIABLE PROTECTION

Reduces repair and maintenance costs of cooling systems

The product name in an order: Coolant LUKOIL ANTIFREEZE HD, STO 79345251-008-2008

### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Color	GOST 28084	from light pink to red
Density at 20 °C, kg/m <sup>3</sup>	GOST 18995.1	1,084
Crystallization temperature, °C	GOST 28084	-41
Boiling temperature, °C	p.7.3 STO	109.2
pH at 20 °C	GOST 22567.5	7.55
Alkalinity, ml	GOST 28084	15.36